



ALUMAX

BATH ENCLOSURES

a product of Alcoa

Tel: 800-643-1514

Fax: 870-234-3181

340/350 Slider Shower Door-Frameless

www.alumaxbath.com

Product Features

- Available in standard and custom configuration
- Tempered safety glass
- Adjustable sealed heavy duty ball bearing rollers
- Up and down adjustment of panels is $\pm .156$
- Safety tee-lock wall jamb to header connection
- Molded jamb bumpers with concealed fasteners
- Molded nylon panel guide of sufficient height to prevent the accidental dislodging of interior panel

Options

- Anti-jamb header insert
- Wall fill
- Curb fill
- Glass patterns
- Finish



Calculations

Maximum allowable width of unit = 72

Maximum allowable height of unit = 72

Glass Size

Width = (Unit Width \div 2)

Height = Unit Ht. - 3

Metal Cuts

SC-556 tub track = Unit width - 1/16

SC-805 towel bar = Glass width - 2 7/8

SC-896 wall jamb = Unit ht. - 1 1/2

SC-917 Header = Unit width - 1/16

340/350 Parts List

- A. 1 Tub Track with Vinyl
- B. 2 Wall Jamb
- C. 6 Plastic Wall Anchors
- D. 6 #8 x 1 1/2 Truss Head Screws
- E. 4 Nylon Spacers
- F. 1 Header
- G. 2 Glass Lites
- H. 4 Hanger Brackets (Pre-assembled)
- J. 2 Trim Rings
- K. 2 Acrylic Towel Bar Brackets
- L. 2 Towel Bar Bases
- M. 2 #10-24 x 1/2 Flat Head Screws
- N. 1 Towel Bar
- P. 4 Vinyl Shims
- R. 2 Pull Handles
- S. 1 Nylon Bottom Guide
- T. 2 #6 x 3/8 Pan Head Screw
- U. 4 Stainless Bumper Inserts
- V. 4 Vinyl Jamb Bumpers

