



ALUMAX

BATH ENCLOSURES

a product of Alcoa

Tel: 800-643-1514

Fax: 870-234-3181

640/650 Slider Shower Door-Framed

www.alumaxbath.com

Product Features

- Available in standard and custom configuration
- Tempered safety glass
- Adjustable sealed heavy duty ball bearing rollers
- Up and down adjustment of panels is $\pm .156$
- Safety tee-lock wall jamb to header connection
- Molded jamb bumpers with concealed fasteners
- Molded nylon panel guide of sufficient height to prevent the accidental dislodging of interior panel

Options

- Anti-jamb header insert
- Wall fill
- Curb fill
- Glass patterns
- Finish



Calculations

Maximum allowable width of unit = 72

Maximum allowable height of unit = 72

Glass Size

Width = (Unit Width \div 2) - 2

Height = Unit Ht. - 4 1/2

Metal Cuts

SC-556 tub track = Unit width - 1/16

SC-805 towel bar = Bottom rail - 11/16

SC-881 header = Unit width - 1/16

SC-882 top rail = (Unit width \div 2) - 1/8

SC-883 bottom rail = (Unit width \div 2) - 1/8

SC-884 side rail = Unit ht. - 2 5/8

SC-896 wall jamb = Unit ht. - 1 1/2

640/650 Parts List

- A. 1 Tub Track with Vinyl
- B. 2 Wall Jamb
- C. 6 Plastic Wall Anchors
- D. 6 #8 x 1 1/2 Truss Head Screws
- E. 2 Nylon Spacers
- F. 1 Header
- G. 2 Glazed Panels
- H. 4 Nylon Roller Bearings
- J. 4 #8-32 x 3/8 Hex Head Screws
- K. 4 Towel Bar Trim Rings
- L. 4 Towel Bar Brackets
- M. 2 Towel Bars
- N. 2 #10-24 x 7/8 Truss Head Screws
- P. 2 #10-24 x 1 1/8 Flat Head Screws
- R. 2 Acrylic Finger Pulls
- S. 2 Alumax Decals
- T. 1 Nylon Bottom Guide
- U. 1 #6 x 3/8 Pan Head Screw
- V. 2 Stainless Bumper Inserts
- W. 2 Soft Jamb Bumpers

